REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED





GENERAL NOTES:

A) Material:
1. Regular Galvanized Wire Per ASTM A641
2. Carbon Steel Brite Basic Wire Per ASTM A510 Grade 1008
3. 304 & 316 Stainless Steel

B) Finish: (Carbon Steel Wire Only)
1. Electrodeposited Zinc, Type III Finish
Service Condition (one) per ASTM B633
2. Polyester Powder Coating 1.2 - 3.0 mils thick

C) Dimensional Tolerances:
1. General Dimensions: +/- 1/8" U.N.O.
2. Length: +/- 1/4"
3. Width: +/- 1/8"
4. Depth: +/- 1/8"
5. Angular Formation: +/- 3°, -0
6. Camber: Shall not exceed 1/2" on standard 10' length
7. Twist: Shall not exceed 1/2" on standard 10' length

D) Rib Wire Diameter
1. .197" (5mm) Diameter

E) Longitudinal Wire Diameter
1. .197" (5mm) Diameter

F) Cross Section Area
Area = (9 Wires)(.0304 in2)= .2736 in2
UL Marking= .2 in2

This drawing in design and detail is the property of WBT, LLC. and must not be used except in connection with our work. All rights of design or invention are reserved.

6 in Horizontal Sweep

CN	SIZE A	Date: 12-15-08	DWG NO.
	SCALE 1:16		SHEET 1 of 1